

			HERMANNSSON ARCHITECTS
	HW	MP, 240 V INSTANT RECEPTACLE (GFI)	
	AT F		CANA MARKEN
	3 SV	VITCHES INSTALLED IN BLOCK	
TANKLESS	ALL BE I	SHOWN, OTHER RECEPTACLES SHALL MOUNTED ON THE SURFACE	2659 SPRING STREET
	AND	O WIRED W/ 1/2" EMT CONDUIT	REDWOOD CITY, CA 94063
	GAI	RAGE NOTES:	Revisions
	SWI	L RECEPTACLES AND	No. Date Description 5/14/2012 submittal 1 9/26/2012 revision1
	TH NEX	IE DATA/TV/PHONE WALL JACKS (T TO THE LIVING/ KITCHEN LL SHALL BE FED BY A 1" PVC	2 3/4/2013 revision2
DOG RUN	CON	NDUIT, SLEEVED, UNDER THE B FROM THE ENTERTAINMENT ITER JACKS.	
	A : SHA	2" PVC CONDUIT, SLEEVED, ALL BE INSTALLED FROM THE AVICE/ METER LOCATION TO THE	
	GAF	RAGE FOR FUTURE POWER	
	A 4		
	-		
	FLE	CTRICAL /	
		CHANICAL KEY	HUGHES
	Ş		RESIDENCE
		SWITCH	RESIDENCE
		THREE-WAY SWITCH	
	Ş ₄	FOUR-WAY SWITCH	
,,,,,,,, .	₽	DUPLEX OUTLET	
PERFORATED PLASTIC DRAIN, 6" DIA., BURIED 12" IN GRAVEL,	⊕ _{DC}	DC OUTLET,	11593 SW ROUNDUP PL.
SLOPE 1/4" / FT TO DAYLIGHT	↓ GFI	W/ DIFFERENT PLUG TYPE	TERREBONNE, OR 97760
		GROUND FAULT INTERRUPT	
	\bigcirc	FLOOR DUPLEX OUTLET	
	\bigoplus	FLOOR QUAD OUTLET	
RECEPTACLES IN THE CONCRETE FOR THE ERTOP RECEPTACLES.	WP WP	WEATHER PROOF OUTLET	
LOWITH RECEPTACLES EVERY 12" IE UPPER CABINETS. LIGHTS UNDER THE UPPER CABINETS SHALL	D	DATA COMPUTER CABLE,	
D NEED A RECEPTACLE FOR A TRANSFORMER R CABINETS TO FEED THEM. E STOVE NEEDS ONE OF THE 120 VOLT		CAT 6 NETWORK WIRE	
TS TO FEED IT. T RANGE RECEPTACLE SHALL BE IN THE HOWN.		TV CABLE	
		TELEPHONE	
		RECESSED CEILING LIGHT	ELECTRICAL/
AULT NOTES:		SURFACE MOUNT LIGHT	MECH
AND VAULT ROOM, THE POWER LED IN THE BLOCK WALLS AS MUCH THE VAULT, THE RECEPTACLE ON	\bigcirc	WALL SCONCE	
DUTER WALL SHALL BE SURFACE 2" EMT CONDUIT INSTALLED FROM IT HT PARAPET.		STRIP UPLIGHT	
R ROOM. IN THE SERVER ROOM, USE			
red LOW VOLT WIRE RACEWAY.		UNDERCABINET STRIP	
		TUBE DOWNLIGHT	
/UST COMPLY WITH ASHRE 62.2	\square	FLOOD LIGHT	
		ELECTRICAL WIRING	
E VENT: 2137 SF X 9.8' X (4 CHANGES/DAY) 58 CFM	\bigcirc	VENT FAN	
NG OF ONE SONE OR LESS.			
VELOCITY RATE GOAL < 100 FPM, 00 FPM PER REFERENCE 1, PAGE 121		CEILING FAN W/ LIGHT	APN: 13-12-05D-02300
D VENT:	s d	SMOKE DETECTOR	DATE: 3/4/2013 DRAWN BY: SM
I INT: FOR EACH BATH.			CHECKED BY: JH
S SOUND RATING OF THREE SONES	+ нв	HOSE BIBB	SCALE: $1/4" = 1'-0"$
TORS SHALL BE CLEARLY AUDIBLE IN S OVER BACKGROUND NOISE	NORTH	AIR SUPPLY REGISTER	SHEET NO:
ALL INTERVENING DOOR CLOSED. TORS SHALL BE HARD WIRED/ TED AND SHALL BE EQUIPPED WITH	TI ~~	AIR RETURN	A-9